

# ENERVEX GSV-012 Motor Replacement

( Due to explicit language, video is unavailable )

## ENERVEX GSV-012 Motor Replacement



Same process compatible with  
GSV009 - GSV014 - GSV016  
RSV009 - RSV012 - RSV014 - RSV016



( **LEFT** ) Remove the Motor Cover to expose the J4 Motor and free the Bird Screen

Remove the safety screws on either side of the Lifting Handle to open the Fan Housing

( **BELOW** ) Evaluate the condition of the Axial Vane and Cooling Vane

Clean and spray as necessary to loosen the hex bolts ( metric )



A "puller" should be used to remove the Axial Vane



Clean and spray the Motor Shaft and loosen the Hex Bolt on the Cooling Vane to remove.



After a brief skirmish sliding off the cooling vane... Murphy's Law applies that only 3 of 4 screws will be easily removable

Impact Driver may be necessary to remove the 4 Motor Mount Screws



Feed the Silicone Cased Motor Wire through the Conduit Fitting of the Fan Housing to remove the Motor with Motor mount

Replacement Motors are supplied pre-wired with 5ft of new Silicone Case Wire for easy replacement.



Motors, Start Capacitors, Axial Vanes, Cooling Vanes, Wire, Conduit, Conduit Fittings and Inlet Collars are in stock at Volko Supply, your EnerVex Fan Source, and available to expedite if necessary

**800 685 8263**

516 741 4466